

## DS-K1T804AMF Fingerprint Access Control Terminal



- Access control fingerprint terminal
- 3,000 fingerprints, 3,000 cards and 100,000 events storage
- Built-in card reader for Mifare1 card
- Communication via TCP/TP and Wi-Fi
- RS-485, wiegand interface
- Alarm input and output interface
- ISUP5.0, ISAPI



## ▪ Specification

<b>Display</b>	
Screen size	2.4-inch
Resolution	320 × 240
Type	LCD-TFT display screen
<b>Audio</b>	
Audio output	1 loudspeaker, 1 buzzer
<b>Network</b>	
Wired network	TCP/IP, 10/100Mbps, self-adaptive
Wi-Fi	Support
<b>Interface</b>	
Network interface	1
RS-485	1
Wiegand	1
Lock control	1
Exit button	1
Door contact input	1
Alarm input	1
Alarm output	1
TAMPER	1
USB	1
<b>Capacity</b>	
Card capacity	3000
Fingerprint capacity	3000
Event capacity	100,000
<b>Authentication</b>	
Card type	Mifare 1 card
Card reading distance	0 to 4.5 cm
Card reading duration	< 1 s
Fingerprint module	Optical fingerprint module
Fingerprint comparing mode	1:1 and 1:N
Fingerprint recognition duration	< 1 s
<b>General</b>	
Indicator	Power/status (red/green)
Power supply	12 VDC/1 A
Working temperature	-10 °C to +55 °C (14 °F to +131 °F)
Working humidity	10% to 90% (no condensing)
Color	Black (included), gold (optional), silver (optional), white (optional)
Dimensions	205 mm × 76.5 mm × 37 mm (8.07" × 3.01" × 1.46")
Installation	Surface mounting

## ▪ Available Model

DS-K1T804AMF

▪ Dimension

